

full line

pH ELECTRODE

Model : PE-03, PE-11, PE-01

ISO-9001, CE, IEC1010

PE-06HDA, PE-04HD, PE-03K7, PE-21



PE-11



PE-03



PE-01



PE-06HDA



PE-03K7



PE-21



PE-04HD

Lutron

LUTRON ELECTRONIC

The Art of Measurement

full line

pH ELECTRODE

pH ELECTRODE Model : PE-03	* General purpose, laboratory and field usage. * 12.3 mm dia. x 160 mm. * Epoxy body, 1 - 13 pH.
pH ELECTRODE Model : PE-11	* General purpose, laboratory and field usage. * 10 mm dia. x 130 mm. * Epoxy body. * 1 - 13 pH. (0 - 14 pH typical)
pH ELECTRODE Model : PE-01	* Professional, laboratory and field usage. * 9.5 mm dia. x 130 mm. * Epoxy body. * 0 - 14 pH.
SPEAR TIP pH ELECTRODE Model : PE-06HDA PE-04HD	* The "Spear Tip pH electrode" is perfect for those pH measurements in applications where sample piercing is required. Meat, sausage and cheese are ideal applications. The electrode features a very durable glass measuring spear packaged in a rugged virtually unbreakable epoxy body. * Range : 0 to 14 pH (PE-04HD) * Range : 1 to 13 pH (PE-06HDA)
pH ELECTRODE + Temp. PROBE (combination kit of pH electrode) Model : PE-03K7	* One kit combine of pH electrode PE-03 and Temp. probe TP-07 as a whole unit. * Easy operation for the pH measurement under the ATC (Automatic Temp. Compensation). * Available for PH-208, PH-207, PH-207HA, PH-221, PH-221E, YK-2005WA., PH-230SD. WA-2017SD, WA-2015, BPH-231, PH-224S, YK-2001PHA.

* Appearance and specifications listed in this brochure are subject to change without notice. 1809-PHELECTRODE